


Access controlled...

Future secured




ETL LISTED No 1010090008MTL-003
ACCORDING TO UL325 AND CSA C22.2#247



Rapid industrial **rising barrier** for vehicle access control at medium and wide access points: industrial sites, traffic management, etc.

Configurations



DESCRIPTION

- Operator cabinet** made of folded and welded sheet metal, ranging from 1/8" to 5/16" [3 to 8 mm] thick.
- Removable side and front doors** with peripheral sealing joint and lock, ensuring easy access to the mechanism (see illustration).
- Removable top cover** (lockable by key).
- LEFT or RIGHT round aluminum arm**, white lacquered with red reflective stripes. The arm is composed of segments of 3.93-3.52-3.29 in [100-90-84 mm] (in diameter) that fit together to obtain lengths from 10 ft [3 m] up to 26.2 ft [8 m]. Arms 23.1 ft [7 m] and longer are braced by galvanized steel cables.
- Solid drive shaft** for the arm, with a diameter of 2 in [50 mm], mounted on 2 life lubricated bearings.
- Electromechanical assembly:**
 - Reversible three-phase asynchronous gear motor, ensuring protection of the mechanism in the event of forced lifting of the arm due to fraud.
 - Secondary transmission via gearwheel and sprocket wheel. Maintaining the arm in its two extreme positions (open and closed), as well as after a STOP command is achieved by means of an electromagnetic brake.
 - Frequency inverter ensuring the progressive accelerations and controlled decelerations of the arm, for a vibration-free movement and enhanced protection of the mechanism.
 - Electronic limitation of the electromechanical assembly torque allowing for the immediate stop of the arm during closing in the event of an obstacle.
 - Inductive limit switches.
 - Balancing of the arm by means of one or more compression springs, depending on the weight of the arm.
- Configurable AS1620 electronic control board** allowing for various control options and/or additional accessories. Among the features of the logic:
 - IP addressable
 - Configurable relays allowing the communication of different barrier status through dry contact.
 - Master-slave command allowing the control of 2 barriers facing each other (movement of one barrier controlled by the other barrier).

ANTI-CORROSION TREATMENT

- Zinc-coated internal mechanical parts.
- Complete body (housing, cover and doors): corrosion resistant primer + powder coat paint (standard color: Orange RAL 2000)



STANDARD TECHNICAL CHARACTERISTICS

Input power ⁽¹⁾	120 VAC / 60 Hz (with ground)
Consumption	450 W (nominal) - 850 W (max. with biggest heater)
Motor	Three-phase 240 V / 250 W controlled by frequency inverter
Transmission	Reversible ring and pinion speed reducer, service factor 1.2
Arm length (L)	9.8 to 26.2 ft [3 to 8m] Increments of 1.63 ft [0.5m]
Operating temperature	14°F to 122°F (-10°C to 50°C)
Relative Humidity	95% without condensation
Wind resistance	74.6 mi/h [120 km/h]
Opening speed ⁽²⁾	5.5 s
Closing speed ⁽²⁾	5.5 s
Weight (without arm)	484 lbs [220 kg]
Weight arm ⁽³⁾	24.2 to 48.4 lbs (11 to 22 kg)
MCBF ⁽⁴⁾	3,000,000 cycles (with recommended maintenance)

- (1) not to be connected to a floating network or to high impedance earthed industrial distribution network
 (2) adjustable through the control board
 (3) Depending on length and without options.
 (4) Mean Cycle Before Failure

STANDARD DIMENSIONS (INCHES & MM)

Refer to the installation drawing for more details.



OPTIONS

1. Automatic opening of the arm during power failure ^(a).
2. Standard adjustable tip support.
3. Electromagnetic tip support.
4. Folding tip support.
5. Folding rigid aluminium skirt. ^(c)
6. Safety edge.
7. STOP sign with a diameter of 300 mm.
8. Traffic lights mounted on a post on housing. ^(c)
9. Traffic lights mounted on a standalone post.
10. Push-button box
11. Key switch
12. Radio transmitter/receiver.
13. Detection loop.
14. Presence detector for inductive loops.
15. Photoelectric cell to open, close or automatically stop the barrier arm
16. Photoelectric cell support post
17. AS1623 Input/Output extension board.
18. AS1049 board for third-party traffic signs.
19. Thermostatic 400W heating for operation down to -49°F [-45°C]
20. Red arm light.
21. Raised base.
22. Rotating base
23. Insulated anti-corrosion base
24. Non-standard RAL colors available.
25. Offset arm stirrup, increasing the stiffness of the arm shaft.
26. Smart Touch monitoring and control panel.

^(a) ^(b) Mutually incompatible options.

^(c) When equipped with these options the barrier is not ETL listed.

For restrictions on options please speak to your sales representative.