ClearLock

Security Booths

AUTOMATIC SYSTEMS

Access Controlled...
Future Secure

Pedestrian

ClearLock

Automatic Systems' ClearLock security doors are cylindrical booths that ensure strict entrance control and are especially designed for sensitive sites. Combining high security and elegance, the ClearLock series is available in different sizes, shapes and finishes, with single or double doors both on entry and exit.

CLEARLOCK 636
Passage width:
27 1/2" (700 mm)
External diameter:
Ø 45 1/4" (1150 mm)
H: 92 1/2" (2350 mm)

CLEARLOCK 637
Passage width:
33 7/16" (850 mm)
External diameter:
Ø 59 1/16" (1500 mm)
H: 92 1/2" (2350 mm)

CLEARLOCK 646
Passage width:
27 1/2" (700 mm)
Footprint:
L: 45 1/4" (1150 mm)
W: 45 1/4" (1150 mm)
H: 92 3/4" (2360 mm)

CLEARLOCK 656
Passage width:
35 1/2" (900 mm)
Footprint:
L: 58 1/2" (1485 mm)
W: 74 3/4" (1900 mm)
H: 94 1/2" (2400 mm)

Security & Safety

- Full-height circular booth with sliding entrance and exit doors that never open simultaneously
- Bullet, vandalism and theft resistant, compliant with industry standards (EN1063, EN356, UL752...)
- Single person detection

Aesthetics & Customization

- Elegant design with large glass surface
- Doors mounted directly onto existing floor
- Compact footprint
- Round or square frame
- Wide range of finishes (stainless steel, painted...)
- Tinted glass obstacles

Adaptability & Flexibility

- Products available disassembled, in accordance with on-site installation requirements
- Electronic and mechanical parts located in the canopy, easily accessible for maintenance
- Numerous accessories available

Reliability & Performance

- Double entrance and exit doors, ensuring fluid throughput (ClearLock 65x)
- Control panel for set up and management
- Remote management using TCP/IP connectivity

Standard Ral Colors

RAL 7035	RAL 9011	RAL 9010	RAL 8019
Light grey	Black	White	Dark brown

All other finishes must be specified when ordering.

1-800-263-6548 www.automatic-systems.com

AUTOMATIC SYSTEMS

NAM-CL-EN (2018-08)